















## SPECIFICATIONS

		SPACIA	SPACIA LOCKSOLID
	CONSTRUCTION	LVT with micro-beveled edges	LVT with micro-beveled edges and locking technology
	AVAILABLE SIZES	4" x 36" (102 x 915 mm), 7.25" x 48" (185 x 1220 mm) Xtra. Sizes are style dependent.	4" x 36" nominal
	WEAR LAYER THICKNESS	20 mil (0.51 mm)	20 mil (0.51 mm)
	OVERALL THICKNESS	.098" (2.5 mm)	.157" (4.0 mm)
	PIECES PER CARTON	27 pcs - 4" x 36"; 9 pcs - 7.25" x 48"	16 pcs
	COVERAGE PER CARTON	27 sq. ft. of 4" x 36"; 21.75 sq. ft. of 7.25" x 48"	14.5 sq. ft.
	3RD PARTY CERTIFICATION	FloorScore, Industry wide 3rd party Type III EPD (Environmental Product Declaration)	FloorScore, Industry wide 3rd party Type III EPD (Environmental Product Declaration)
	LEED	Mannington Commercial products may contribute to multiple LEED credits.	
	QUANTUM GUARD® HP	The highest performance commercial urethane finish in the industry. The patented aluminum oxide proprietary wear layer eliminates the need for polish, while enhancing durability, cleanability, appearance retention, and slip retardance when compared to standard LVT floors - resulting in 70% annual savings in maintenance costs.	
	RAPIDLY RENEWABLE CONTENT	Contains 3% rapidly renewable resource content.	
	QUICKSTIX®	LVT with pre-applied adhesive, reducing time and labor required to install the flooring. QuickStix® floors can be used immediately after installation, even in extreme moisture areas.	N/A
	US MANUFACTURING	Mannington is a fourth generation, family-owned company deeply committed to U.S. manufacturing. We make flooring in seven communities across the U.S., allowing us to provide the highest levels of service and quality in the industry, while supporting local economies and crafting quality, American-made products.	
	WARRANTY	This product is backed by our Limited 10 Year Commercial Warranty and Limited 10 Year Quantum Guard® HP Wear Warranty.	This product is backed by our Limited 10 Year Commercial Warranty, Limited 10 Year No Gap Warranty, and Limited 10 Year Quantum Guard® HP Wear Warranty.
	XPRESS	When you really need it now. Our innovative delivery program ensures that you get the carpet and hard surface products you need quickly and reliably. With product available to ship within 5 business days, Mannington's Xpress program leads the industry in service. Please refer to manningtoncommercial.com to view Xpress products.	
STATIC LOAD LIMIT		(Modified @1000 PSI): Pass	
SPECIFICATIONS (ASTM F1700)		Class 3, Type B	Class 3, Type B Embossed Surface
HEAT STABILITY (ASTM F1514)		Passes	
STAIN & CHEMICAL RESISTANCE (ASTM F925)		Passes	
COEFFICIENT OF FRICTION (COF)		≥ 0.5 Leather; 0.6 Rubber	
FLOORING RADIANT PANEL (ASTM E648)		Passes - Class 1	
N.B.S. SMOKE CHAMBER (ASTM E662)		< 450, Passes	
IMPACT SOUND TRANSMISSION (ASTM E90/ASTM E492 - IIC 6" CONCRETE WITH DROP CEILING		IIC ≥ 50 IIC ≥ 62 over Mannington Silent Solution	IIC ≥ 50 IIC ≥ 63 over Mannington Silent Solution or Whisper 3N1
INSTALLATION ADHESIVE		Porous & Non-Porous Substrates: Amtico High Pressure Sensitive, Full Spread / RH 90%, MVER 8, pH5-9; Amtico 373, Full Spread / RH 80%, MVER 5, pH 7-10; XpressStep for LVT Spray Adhesive / RH 90%, MVER 8, pH11; XpressStep Premium Spray Adhesive / RH 93%, MVER 10, pH12. Non-Porous Substrates or where higher performance is required: Amtico Universal, Full Spread, 2 Part Urethane / RH 80%, MVER 5, pH 7-10. Under Hospital Beds and Heavy Rolling Loads: Amtico Universal, Full Spread, 2 Part Urethane / RH 80%, MVER 5, pH 7-10; XpressStep for LVT Spray Adhesive / RH 90%, MVER 8, pH11; XpressStep Premium Spray Adhesive / RH 93%, MVER 10, pH12. QuickStix® pre-applied adhesive / 99% RH, MVER 18, pH12	Spacia LockSolid utilizes a proprietary and patented locking system that does not require adhesive. Whisper 3N1 Underlayment or Mannington Silent Solution Underlayment are optional for all grades: above, on, and below. Whisper 3N1 Underlayment or Mannington Silent Solution Underlayment should not be used in heavy rolling load areas.

Note: The following products are sourced: Antique Oak SS5W2507 and Ember Oak SS5W2512. Please contact your local Mannington representative for more information.



**MANNINGTON**  
COMMERCIAL