SPECIFICATIONS		SPACIA FIRST	SPACIA FIRST 20
Ø ₀	CONSTRUCTION	LVT with micro-beveled edges	
_	AVAILABLE SIZES	12" x 12" (305 x 305 mm), 12" x 24" (305 x 610 mm), 18" x 18" (457 x 457 mm), 6" x 36" (152 x 915 mm), 7.25" x 48" (185 x 1220 mm). Sizes are style dependent.	6" x 36" (152 x 915 mm) and 7.25" x 48" (185 x 1220 mm). Sizes are style dependent.
×	WEAR LAYER THICKNESS	12 mil	20 mil
×	OVERALL THICKNESS	0.08" (2.0 mm)	0.098" (2.5 mm)
*	COVERAGE PER CARTON	27 sq. ft. of 12" x 12"; 38 sq. ft. of 12" x 24"; 27 sq. ft. of 18" x 18"; 27 sq. ft. of 6" x 36"; 21.75 sq. ft. of 7.25" x 48	27 sq. ft. of 6" x 36"; 21.75 sq. ft. of 7.25" x 48"
**	PIECES PER CARTON	27 pcs - 12" x 12"; 19 pcs - 12" x 24"; 12 pcs - 18" x 18"; 18 pcs - 6" x 36"; 9 pcs - 7.25" x 48"	
Ø	3RD PARTY CERTIFICATIONS	FloorScore, Industry wide 3rd party Type III EPD (Environmental Product Declaration)	
@	LEED	Mannington Commercial products may contribute to multiple LEED credits.	
10	WARRANTY	Spacia First is backed by our Limited 10 Year Light Commercial Warranty. Spacia First 20 is backed by our Limited 10 Year Commercial Warranty.	
STATIC LOAD LIMIT		750 PSI	
SPECIFICATION (ASTM F1700)		Class 3, Type B	
HEAT STABILITY (ASTM F1514)		Passes	
STAIN & CHEMICAL STABILITY (ASTM F925)		Passes	
HUD/FHA REQUIREMENTS		Exceeds	
AMERICANS WITH DISABILITIES ACT GUIDELINES (ADAG)		Meets or exceeds ADA Guidelines	
COEFFICIENT OF FRICTION (COF)		≥ 0.5 Leather; 0.6 Rubber	
FLOORING RADIANT PANEL (ASTM E648)		Passes - Class 1	
N.B.S. SMOKE CHAMBER (ASTM E662)		< 450, Passes	
INSTALLATION ADHESIVE		Amtico 373 / Full Spread Porous & Non-Porous Subfloor, Amtico PS - High Moisture Adhesive / Transitional Pressure Sensitive/ Full Spread Porous & Non-Porous Subfloor, Amtico Universal 2-Part/ Full Spread Non-Porous Subfloor, XpressStep Spray Adhesive / RH 90%, MVER 8, pH 11, XpressStep Premium Spray Adhesive / RH 93%, MVER 10, pH 12. Note: Must use Amtico Universal 2-Part or XpressStep Adhesive under hospital beds and heavy rolling loads or where high performance is needed.	







